

**Support Services:**

11 Bruce Roderick Drive,  
East Tamaki, Auckland 2013

Ph: (09) 276 0760



Konnect is a registered trademark of Coventry Group (NZ) Ltd. NZBN 9429037435394 T/as Konnect Fastening Systems

## BUILDING PRODUCT INFORMATION SHEET

Product Name:

**CLASS 1**

Place of Manufacturer: **New Zealand**  **Overseas**  (please tick applicable)

Legal and Trading name of the Manufacturer(s):

We source our products from various quality approved Overseas manufacturers. For details relating to a product batch or lot number you intend to purchase please contact the team on [BPiRenquiries@konnectshop.com](mailto:BPiRenquiries@konnectshop.com) for additional specific information.

Legal and Trading name of the Importer (if applicable):

Address for Service:

STREET NAME  SUBURB

CITY, COUNTRY  POSTCODE

Website	<input type="text" value="konnectfasteningsystems.co.nz"/>
Email Address	<input type="text" value="BPiRenquiries@konnectshop.com"/>
Phone No (if applicable)	<input type="text" value="0508 566 632"/>
NZBN (if applicable)	<input type="text" value="9429037435394"/>

Product Identifier/Drawing (if applicable):



Product Description:

Konnect Aquaseal and Aquadapts are exterior flexible flashings for cylindrical penetrations to roof cladding. Aquaseals and Aquadapts are comprised of either an EPDM or Silicone rubber cone and flange, with a malleable aluminium perimeter that is moulded to the roof cladding and fixed with fastenings and sealant.

**Support Services:**

11 Bruce Roderick Drive,  
East Tamaki, Auckland 2013

Ph: (09) 276 0760



Konnect is a registered trademark of Coventry Group (NZ) Ltd. NZBN 9429037435394 T/as Konnect Fastening Systems

**Scope of Use**

Aquadapts and Aquaseals are designed for water tightness around pipe penetration in Roofing and Cladding application

**Limitations**

Do not directly install on roof pitches below 8 Degrees on corrugated profiles. When fitted to a correctly sized flat soaker do not install below 10 Degree pitch for corrugated iron and 3 Degree pitch for trapezoidal or trough sections. Roof boots fitted below 8 Degree pitch should not be installed at 45 Degrees to the profile. Aquaseals and Aquadapts are installed with a malleable aluminum perimeter that can be moulded to the roof profile and either be fixed with fasteners or sealant

**Materials**

Polymer is ozone and UV resistant, has a 20 year warranty. EPDM will withstand constant temperatures of -40C to 115C

**Installation**

As per the code of practice

**Maintenance**

None Required

**Support Services:**

11 Bruce Roderick Drive,  
East Tamaki, Auckland 2013

Ph: (09) 276 0760



Konnect is a registered trademark of Coventry Group (NZ) Ltd. NZBN 9429037435394 T/as Konnect Fastening Systems

**Compliance with NZ Building Code (NZBC):** In alphabetical order

Konnect Roofing Fastener Systems will contribute to compliance with the following clauses of the New Zealand Building Code.

**NZBC B1 Structure**

Konnect Roofing Fastener Systems structural strength complies with AS/NZS 3566 section. Pull out values have been tested in accordance with recommendations in the Metal Roofing Code of Practice.

**NZBC E2 External Moisture**

The sealing washers used for Konnect Fastening Systems comply with AS/NZS 3566 section.

**NZBC F2 Hazardous Building Materials**

Konnect Fastening Systems meet the performance requirements of F 2.3.1.

**Is the building product/building product line subject to warning or ban under section 26 of the Building Act 2004?**

Yes  No

If yes, description of the warning or ban under section 26:

Version

Date